

Huebsch is the answer.



Vended
30 and 45 lb
Stack Tumble Dryers



 **Huebsch®**

30 and 45 lb Stack Tumble Dryer Specifications

Models	HTT30	HTT45	
Control Options	Galaxy™ 600, Basic Electronic	Galaxy™ 600, Basic Electronic	
Dry Weight Capacity - lb (kg)	2 x 30 (13.6)	2 x 45 (20.4)	
Width - in (mm)	31 1/2" (800)	34 1/2" (876)	
Depth - in (mm)	42 3/4" (1086)	48 5/8" (1235)	
Height - in (mm)	76 1/4" (1937)	81" (2059)	
Cylinder Depth - in (mm)	26" (660)	30" (762)	
Cylinder Diameter - in (mm)	30" (762)	33" (838)	
Cylinder Volume - cu. ft. (liters)	10.6 (301)	14.8 (421)	
Door Opening Size - in (mm)	22 11/16" (576)	26 7/8" (683)	
Airflow - cfm (liters/sec.)	50 Hz: 340 (160) 60 Hz: 400 (189)	50 Hz: 500 (236) 60 Hz: 600 (283)	
Energy Data	Gas Models: 50 Hz: 73,000 Btu/hr (21.4 kW) Per Pocket 60 Hz: 73,000 Btu/hr (21.4 kW) Per Pocket Steam Models: At 100 psi (6.9 bar): 3.2 BHP 111,000 Btu/hr (32.5 kW) Electric Models: 21 kW	Gas Models: 50 Hz: 87,000 Btu/hr (25.5 kW) Per Pocket 60 Hz: 95,000 Btu/hr (27.8 kW) Per Pocket Steam Models: N/A Electric Models: N/A	
Electrical Specifications	Gas and Steam 100/200-220/60/1 2W+G 200/60/1 2W+G 120/208-240/60/1 2W/3W+G 208-240/60/1 3W+G 200-208/240/60/3 3W+G 380/60/3 3W+G 460-480/60/3 3W+G 100/200/50/1 2W+G 200/50/1 2W+G 230-240/50/1 2W+G 200/50/3 3W+G 230-240/50/3 3W+G 380/400-415/50/3 3W+G Electric 200-208/60/3 3W+G 240/60/3 3W+G 380/60/3 3W+G 460-480/60/3 3W+G 200/50/3 3W+G 230-240/50/3 3W+G 380/50/3 3W+G 400-415/50/3 3W+G	Amps: 22.0/11.6 N/A 16.0/8.0 N/A 6.4/6.4 3.0 3.3 24.2/15.0 N/A 15.0 5.8 7.0 3.0/3.2 62/PKT 54/PKT 33/PKT 27/PKT 60/PKT 55/PKT 33/PKT 31/PKT	Amps: N/A 11.2 N/A 12.0 9.6/9.6 N/A N/A 11.2 10.8 N/A N/A N/A
Plumbing Connections - in	Gas: 1/2" - NPT Steam: 3/4" - NPT	Gas: 1/2" - NPT	
Shipping Dimensions	Width: 32 1/2" (825) Depth: 47" (1194) Height: 81" (2057)	Width: 35 1/2" (902) Depth: 54" (1372) Height: 85" (2159)	
Net Weight - lb (kg)	544 (247)	673 (305)	
Shipping Weight - lb (kg)	582 (264)	718 (326)	
Agency Approvals	cCSAus, CE	cCSAus, CE	

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. USA and Canada models are certified by C.S.A International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A. ©Copyright 2013 Alliance Laundry Systems LLC

Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120