



Washer extractors

Fast Spin washer extractors TP

FAST SPIN WASHER, LR-14 TP HW

DIMENSIONS

		Article	Packed
Length	mm	719,00	800,00
Depth	mm	810,00	990,00
Height	mm	1.158,00	1.350,00
Weigth	Kg	239,00	247,00
Volumen	m3		1,07

ELECTRICITY

Electric power	KW	
230V -1+N		2x1,5+T-10A
230V - III		NO
400V - III+N		NO

WATER

Water consumption (lit/h)	168,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 60,00

FAST SPIN WASHER EXTRACTOR, LR-14 TP HW

Made of stainless steel.
Capacity: 14 kg (1:9) or 13 kg (1:10).
Microprocessor "Touch Plus Control" with display.
26 pre-set programs (4 economic programs).
Possibility of programming, export and import programs through USB memory, without limite.
"WASH CONTROL" management software included.
Digital sequence display.
8 signals for automatic liquid dosing, programmable in time and delay.
Possibility to install an automatic detergent doser on the rear of the machine.
Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and softeners).
Water levels completely modifiable.
3 water inlets (Hot water, Cold water, Soft water).
WET CLEANING SYSTEM:
-Water levels completely modifiable.
-Possible manual dosing for evey 8 signals during the cycle.
-Minimum washing speed: 15 r.p.m.
-Minimum thyrhm ON-OFF: 1 second.
Safety switch for door opening.
Wash and spin speeds are configurable.
These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.
Hard mounted machine. Machine must be fixed to the floor. Elements not included
Drum diameter: 620 mm.
Deeeth drum: 430 mm.
Door diameter: 373 mm.
Spin speed: 760 r.p.m.
G Factor: 200.
Easy to attach automatic dossier dispenser at rear of machine.
Water consumption in program n° 2 60°: 135 litres.
Heating system: hot water
Washing process with hot water.
Total power: 1,50 kW.
Dimensions: 719 x 810 x 1.158 mm

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	108	0	1.022		0
SOFT COLD WATER	440	0	1.196	3/4"	
DRAIN	252	0	80	3"	
COLD WATER	650	0	1.216	3/4"	
HOT WATER	495	0	1.196	3/4"	

